



CE

SPECIFICATIONS

Insulation Resistance

Test voltage (DC V)	250V / 500V / 1000V
Measuring ranges	0-100ΜΩ / 0-200ΜΩ / 0-400ΜΩ
Output voltage on open circuit	Rated test voltage +10%
Accuracy	±5% of indicated value
Short circuit current	2mA DC
Power consumption	190mA

Continuity

Measuring range	0-50Ω & ∞
Accuracy	± 5% of scale length
Open circuit voltage	4V DC Approx.
Short circuit current	145mA DC Approx.
Power consumption	200mA

ANALOGUE INSULATION TESTER

- High quality Taut Band movement.
- Battery operated.
- Solid state circuitry.
- Battery check feature.
- Automatic circuit discharge.
- Three insulation test voltages(DC) : 250V, 500V, 1000V
- Continuity test : 50 Ω
- AC voltage measurement : 500V
- Color-coded scale.
- Fuse protected.

AC Voltage

Range	0-500V AC
Accuracy	± 2.5% of full scale
Line frequency range	40 -1k Hz

General

Dimensions (with housing front cover)	175(L) × 85(W) × 75(D)mm
Weight (battery included)	Approx. 600g
Power source	1.5V (AA) × 8
Safety standard	EN 61010-1 CAT III 500V EN 61326-1
Accessories	Instruction manual Test leads Shoulder belt Batteries

STANDARD ELECTRIC WORKS CO., LTD. www.sew.com.tw 5F., NO.105, JHONGCHENG RD., TUCHENG DIST., NEW TAIPEI CITY 23674, TAIWAN (R.O.C.) TEL: 886-2-22681528 FAX: 886-2-22681529 e-mail: sales@sew.com.tw

^{Model} 1180 IN