MEASURE WITH PRECISION

www.sew.com.tw

5F., NO.105, Jhongcheng Rd., Tucheng Dist., New Taipei City 23674, Taiwan (R.O.C.) TEL: 886-2-22681528 FAX: 886-2-22681529 e-mail: sales@sew.com.tw

Analogue Multi-function Insulation/Voltage/ Earth Resistance Tester



4167 MF

FEATURES

- High Quality Taut Band movement.
- Capable of measuring earth resistance and earth voltage.
- 2mA measuring current permits the testing of earth resistance without tripping earth leakage current breakers in the circuit under test.
- The test leads are supplied as standard accessories for simplified two-wire measuring system.
- Two insulation test voltages (DC V) : 250V and 500V.
- Alternation voltage measurement.
- Battery life indicator.
- Fuse protected.

SPECIFICATIONS

Earth Resistance

Measuring system		ce by constant r 820Hz, 2mA
Measuring Ranges	Earth resistan 0-12/0-120 Earth voltage: 0-30V AC	/0-1200Ω
Accuracy	Earth resistand ±3% F.S. Earth voltage: ±2.5% F.S.	ce:
Insulation		
Test voltage(DC V)	250V	500V
Measuring ranges	0-100MΩ	0-200ΜΩ
Output voltage on open circuit	Rated test voltage +10%	
Short circuit terminal current	2mA DC	
Accuracy	± 5% of scale length	
ACV		
AC voltage range	0-600V	
Accuracy	± 2.5% of full scale	


General

Line frequency range

General	
Dimensions	250(L) × 190(W) × 110(D)mm
Weight (battery included)	Approx. 1500g
Power source	1.5V (AA) × 8
Safety standard	EN 61010-1 CAT III 600V EN 61326-1
Accessories	Instruction manual Test leads Auxiliary earth spikes Simplified measurement probe Shoulder belt Batteries

40-500Hz

Insulation Test Connections



Earth Resistance Measurement