

AC Clamp Meter




ST-2600

FEATURES

- Full auto range for V.A and Ω functions.
- Data hold function freezes the reading in dimly lit or hard to reach places.
- Low battery indication.
- Built-in buzzer for continuity test.
- Safety design throughout with no exposed metal parts. Shielded banana plugs and recessed input terminals.
- Ohm function ideal for checking continuity of relays transformers and motor coils.

SPECIFICATIONS

AC A	400A $\pm(2.0\%rdg+3dgt)$: 50/60Hz
AC V	400 / 600V $\pm(1.2\%rdg+3dgt)$: 40-500Hz
Ω	4k Ω $\pm(1.5\%rdg+3dgt)$
Buzzer sounds	< 100 Ω
Conductor size	27mm Max.
Low battery Indication	
Dimensions	197(L) \times 65(W) \times 33(D)mm
Weight (battery Included)	Approx. 250g
Power source	9V(6F22) \times 1
Safety standard	EN 61010-1 CAT II 600V EN 61010-2-32
Accessories	Instruction manual Test leads Soft pouch Battery



ST-3620

FEATURES

- 3½ digit liquid crystal display with maximum reading of 1999.
- Over range indication : "1" is displayed on highest digit.
- Low battery indication: "B" sign appears on the display.
- Response time: approx. 1 second.
- Data hold: for all ranges

SPECIFICATIONS

AC A	200 / 1500A $\pm(2.0\%rdg+4dgt)$ (40Hz-1kHz)
AC V	200 / 750V $\pm(1.5\%rdg+2dgt)$ (40Hz-1kHz)
Ω	200 Ω $\pm(1.5\%rdg+2dgt)$
Buzzer	Resistance is less then 30 Ω
Peak hold	$\sqrt{\quad}$
Conductor size	55mm Max.
Operating temperature	0°C ~ 40°C
Humidity	85%
Current consumption	Approx. 10mA
Dimensions	245(L) \times 70(W) \times 41.7(D)mm
Weight (battery Included)	Approx. 480g
Power source	9V(6F22) \times 1
Accessories	Instruction manual Test leads Soft pouch Battery



AL-24-1

CAC-600
(For ST-2600)CAC-3600 B
(For ST-3620)