

Audio Impedance Tester




1506 IM

FEATURES

- High quality Taut Band movement.
- Battery operated.
- Timer function for hands free use.
- Battery indicator.
- The tester measure with a frequency of 1kHz.
- Measure speaker's impedance.
- Measure speaker lines (connected to load).
- Help to calculate and check audio power systems.
- Ideal for public address installation and maintenance.
- Measure transformer impedances.

SPECIFICATIONS

Measuring system	Constant current inverter with 1kHz approx. 2mA
Measuring ranges	20Ω / 200Ω / 2kΩ
Accuracy	± 2.5% of full scale
Dimensions	163(L) × 100(W) × 50(D)mm
Weight (battery included)	Approx. 420g
Power source	1.5V (AA) × 6
Safety standard	EN 61010-1 CAT II 100V
Accessories	Instruction manual Test leads Carry case Batteries





2706 IM

FEATURES

- True measurement of speaker systems actual impedance at 1kHz.
- Three test ranges (20Ω / 200Ω / 2000Ω) allow testing of home theater and commercial sound systems.
- Measures transformer impedances.
- Battery operated.
- Low battery indication.
- Data hold function.
- Timer function for continuous hands free operation
- The timer can last about 3-5 minutes when users press TEST ON/OFF button.

SPECIFICATIONS

Measuring ranges	0-20Ω / 0-200Ω / 0-2000Ω
Test frequency	1kHz
Accuracy	20Ω : ± 2%rdg±2dgt or ± 0.1Ω, which is greater 200Ω / 2000Ω : ± 2%rdg±2dgt
Low battery indication	"  +" Symbol appears on the display
Data hold indication	"  " Symbol appears on the display
Display	LCD 3½ digit (2000 counts)
Dimensions	205(L) × 90(W) × 55(D)mm
Weight (battery included)	Approx. 530g
Power source	1.5V (AA) × 6
Safety standard	EN 61010-1 CAT III 300V EN 61326-1
Accessories	Instruction manual Test leads Carry case Batteries